# INDIANA LIMESTONE - FULL COLOR BLEND<sup>TM</sup>

LIMESTONE



### DESCRIPTION

A natural, full range compilation of warm buff colors and medium gray tones are present within this historic limestone. Subtle veining meanders throughout the surface creating a unique movement in this medium grained, standard grade stone.

Bush-Hammered

Wire Brushed

QUARRY OPERATING SINCE

ANNUAL PRODUCTION 12 000 m<sup>3</sup> and more (423 776 cu. ft.)

Split Face

Tumbled

#### **AVAILABLE FINISHES**

Honed Sandblasted

Exterior

Interior

Horizontal

**APPLICATIONS** 

Vertical Commercial Residential

## PHYSICAL TEST RESULTS

		Imperial	Metric
Absorption by weight	ASTM C97	7.5%	7.5%
Density	ASTM C97	144 lb/ft <sup>3</sup>	2 306.66 kg/m <sup>3</sup>
Compressive strength	ASTM C170	4 000 Psi	27.58 MPa
Modulus of rupture	ASTM C99	700 Psi	4.83 MPa

#### NATURALLY SUSTAINABLE™

Health Product Declaration® available2020ANSI/NSC 373 Certified Quarry since2018



QUARRY OWNERS | BLOCKS | SLABS | TILES | LANDSCAPING PRODUCTS | CURBS

## polycor.com

Computer generated images and printed reproductions may not accurately match natural stone colors.





